

	SOLID-510S	SOLID-510D	SOLID-510L
Print Type	Dye-Sublimation		
Resolution	300dpi (Color & Mono), 600 & 1200dpi (Mono Only) / Edge to Edge		
Dual Side Printing	Option (with Flipper)	Yes	Yes
Card Feeding	Automatic		
Card Size	ISO CR80 or ISO CR79 (Option-Factory installed)		
Card Thickness	0.38mm (15mil) ~ 1.0mm (40mil)		
Card Type	PVC, PET, Composite PVC	PVC, PET, Composite PVC	Rewritable Thermochromic Material
Monochrome	5 sec./card	5 sec./card	5 sec./card
YMCKO	Max. 17 sec./card	Max. 17 sec./card	Max. 17 sec./card
YMCKOK	-	Max. 22 sec./card	Max. 22 sec./card
Input Hopper	100 Cards / 200 Cards with Cover open		
Output Hopper	Front: 40 Cards / Rear: 100 Cards (Optional Rear-side Stacker)		
Control Panel	1 LED Button		
Supported Platforms	Microsoft Windows 7/ 8 /10, Mac OS, Linux		
Communication	USB / Ethernet, WiFi (Option)		
Power Supply	DC 24V		
Power Consumption	48	48	96
Temperature	15~35℃		
Humidity	35~70%		
WxLxH (Millimeter)	165 x 390 x 210	165 x 498 x 210	165 x 675 x 210
WxLxH (Inch)	6.5 x 15.4 x 8.3	6.5 x 19.6 x 8.3	6.5 x 26.6 x 8.3
Kg/lbs	4.5 /10	5.2 / 11.5	8.8 / 19.4
Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II		
Contact	ISO 7816 (ID-1)		
Contactless	MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS		
Certifications	CB, CE, FCC, KC, CCC		